

WLK Series Liquid Cooling System

The WLK31 is a compressor-based recirculating chiller that offers dependable, compact performance by controlling the temperature of water or water with glycol (antifreeze) in a liquid circuit. The coolant is recirculated using a pump with high MTBF. Heat from the coolant is absorbed by a durable, compressor-based system and dissipated to the ambient environment. The unit is regulated with an easy-to-use digital temperature controller with push button interface. The unit is housed inside a rugged sheet metal casing. Standard cooling capacities range are available up to 3 KW. However, custom solutions have been designed to remove up to 200 KW of heat.

Features

- Cooling to below ambient
- High heat pumping capacity
- Variable temperature control
- High temperature stability
- CFC free refrigerants
- Long life operation

Applications

- [Cooling Particle Accelerators: Linear Accelerators and Cyclotrons](#)
- [Spindle Screw Pump Technology for Medical Cooling](#)
- [Semiconductor Fabrication Equipment Cooling](#)
- [X-ray Cooling in Industrial Scanners](#)



TECHNICAL SPECIFICATIONS

Performance

Cooling Capacity	3,000 Watts
Nominal Operating Flowrate (60 Hz)	6.0 L/min @ 4.0 Bar
Nominal Operating Flowrate (50 Hz)	6.0 L/min @ 4.0 Bar

Operation

Operating Temperature	5°C to 35°C
Storage temperature range (w/o coolant)	-25°C to 70°C
Humidity range	20% to 80%
Storage Humidity range	5% to 95%, non-condensing
Input Voltage	230 VAC
Frequency	50/60 Hz

Physical

Height	920 mm
Length	590 mm
Width	610 mm
Weight	115 kg

NOTES

Any information furnished by Laird and its agents, whether in specifications, data sheets, product catalogues or otherwise, is believed to be (but is not warranted as being) accurate and reliable, is provided for information only and does not form part of any contract with Laird. All specifications are subject to change without notice. Laird assumes no responsibility and disclaims all liability for losses or damages resulting from use of or reliance on this information. All Laird products are sold subject to the Laird Terms and Conditions of sale (including Laird's limited warranty) in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2020 Laird Thermal Systems GmbH. All Rights Reserved. Laird, Laird Technologies, Laird Thermal Systems, the Laird Logo, and other word marks and logos are trademarks or registered trademarks of Laird Limited or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

Date: 04/24/2020